



- DNV 2.7-1
- EN12079
- Cargo securing points inside
- Available fully galvanized
- Flemish splice sling option

Our baskets are designed and built to DNV 2.7-1 / EN12079 standards capable of handling the dynamic loads inflicted on them by lifting operations between moving vessels in the harshest of environments.

These baskets provide a high wall design to ensure compliance with oil majors lifting practices for taller equipment.

They have been designed to fit inside our larger containers so the transportation cost of returning empty equipment after project completion is as efficient as possible.

## CONTACT INFORMATION

Sales@simmondsequipment.com  
TEL- +1 877 271 7466  
www.simmondsequipment.com

# 8' x 6' Basket

SOCIAL NETWORKING



## Additional Benefits



Baskets can be stacked empty for efficient use of client yard space

## Container Dimensions

Classification		Dimension	
<b>External</b>	Length	2500 mm	8' – 2.27/64"
	Width	2038 mm	6' – 8.7/32"
	Height	1535 mm	5' – 7/8"
<b>Internal</b>	Length	2284 mm	7' – 5.59/64"
	Width	1822 mm	5' – 11.3/4"
	Height	1244 mm	4' – 31/32"
<b>Tare Weight (+-2%)</b>		1120 KGS	2470 LBS
<b>Max. Gross Weight</b>		6500 KGS	14330 LBS
<b>Max. Payload</b>		5380 KGS	13210 LBS

### Headquarters

158 N Tunnel Road  
Belle Chasse,  
Louisiana 70037

+1 (504) 394-7466

### Houston Location

12235 FM 529  
Houston,  
Texas 77041

TEL- +1 877 271 7466