



- DNV 2.7-1
- EN12079
- Cargo securing points inside
- Available fully galvanized
- Flemish splice sling option

Our baskets are designed and built to DNV 2.7-1 / EN12079 standards capable of handling the dynamic loads inflicted on them by lifting operations between moving vessels in the harshest of environments.

These come with the options of either tie down rings inside or ratchet winches for webbing straps .

Structurally robust to endure the rigors of long term offshore use. Includes tag line D-rings on all four sides for easy orientation.

Weights and dimensions in both metric and standard are displayed on the outside of the basket.

CONTACT INFORMATION

Sales@simmondsequipment.com
TEL- +1 877 271 7466
www.simmondsequipment.com

8' X 4' Baskets

SOCIAL NETWORKING



Additional Benefits



Headquarters

158 N Tunnel Road
Belle Chasse,
Louisiana 70037

+1 (504) 394-7466

Houston Location

12235 FM 529
Houston,
Texas 77041

TEL- +1 877 271 7466

Baskets can be stacked empty for efficient use of client yard space. Weights and payloads below may change slightly based on whether the units are painted, galvanized or both

Container Dimensions

Classification		Dimension	
External	Length	2440 mm	8'
	Width	1280 mm	4' - 2 25/64"
	Height	1280 mm	4' - 2 25/64"
Internal	Length	2360 mm	7' - 8 29/32"
	Width	1050 mm	3' - 5 21/54"
	Height	983 mm	3' - 2 11/16"
Tare Weight (+-2%)		1000 KGS	2205 LBS
Max. Gross Weight		5000 KGS	11025 LBS
Max. Payload		4000 KGS	8820 LBS