



- DNV 2.7-1
- EN12079
- Available fully galvanized
- Flemish splice sling option
- Aluminum Lid w/ Lift Assistance

Our baskets are designed and built to DNV 2.7-1 / EN12079 standards capable of handling the dynamic loads inflicted on them by lifting operations between moving vessels in the harshest of environments.

Structurally robust to endure the rigors of long term offshore use. Includes tag line D-rings on all four sides for easy orientation.

Weights and dimensions in both metric and standard are displayed on the outside of the basket.

CONTACT INFORMATION

Sales@simmondsequipment.com
TEL- +1 877 271 7466
www.simmondsequipment.com

Tool Box

SOCIAL NETWORKING



Headquarters

158 N Tunnel Road
Belle Chasse,
Louisiana 70037

+1 (504) 394-7466

Houston Location

12235 FM 529
Houston,
Texas 77041

TEL- +1 877 271 7466

Classification		Dimension	
External	Length	1220 mm	48"
	Width	914 mm	36"
	Height	710 mm	24"
Internal	Length	1172 mm	46"
	Width	786 mm	31"
	Height	447 mm	18"
Tare Weight (+-2%)		310 KGS	682 LBS
Max Payload		690 KGS	1518 LBS
Max Gross Weight		1000 KGS	2205 LBS

Classification		Dimension	
External	Length	2490 mm	98"
	Width	1016 mm	40"
	Height	1112 mm	38"
Internal	Length	2442 mm	96"
	Width	888 mm	35"
	Height	879 mm	35"
Tare Weight (+-2%)		650 KGS	1430 LBS
Max Payload		2350 KGS	5170 LBS
Max Gross Weight		3000 KGS	6600 LBS

Classification		Dimension	
External	Length	3556 mm	140"
	Width	1066 mm	42"
	Height	1061 mm	38"
Internal	Length	3508 mm	138"
	Width	938 mm	37"
	Height	828 mm	33"
Tare Weight (+-2%)		880 KGS	1936 LBS
Max Payload		2120 KGS	4664 LBS
Max Gross Weight		3000 KGS	6600 LBS

Please note that other sizes and dimensions can be provided upon request.